

# DP-860

## Compact Size with Integrated HulaPoint II™

The small footprint DP-860 is built for versatility and convenience. It features 84-key functionality and an integrated HulaPoint II™, an upgraded pointing device that offers improved sensitivity and increased durability. Constructed with a sealed, industrial silicone keypad and NEMA 4X protection, the DP-860 is ideal for mobile applications and space saving. In addition, its integrated HulaPoint™ pointing device eliminates the need for an external mouse.



## Technical Specifications

### Certifications

NEMA 4X  
UL60950, FCC Part 15 Class B

### Key Switch

MATERIAL: Industrial silicone rubber  
LIFE: 10 million cycles  
TRAVEL: 0.055  
ACTUATION FORCE: 200g (+/- 20g)  
FEEDBACK: Tactile with mechanical snap

### Power

KEYBOARD: 5V@ 10 ma (from CPU port)  
HULAPOINT: 5V@ 10 ma (from mouse conn. port)

### Temperature Range

STORAGE: -40C to +70C  
OPERATING: -20C to +60C

### Humidity

100%

### Shock

3x11 ms pulses of 50g on each of 3 axes

### Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz  
FREQUENCY RANGE: 20Hz - 2 kHz  
DURATION OF TEST PER AXIS: 3 hours

### Flammability

PRINTED CIRCUIT BOARD: 94 VO  
SILICONE OVERLAY: 94HB  
INTERFACE CABLE: 94 VO

### Weight

3 lbs (1.38 kg)

### Dimensions

11.40" x 6.30" x 1.86" (w-h-d)  
289.56mm x 160.02mm x 47.24mm

### Cable

LENGTH: 4 ft coiled (1.2m)  
DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB

### Compatibility

PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems  
USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS

### Warranty

1 year limited warranty

### Model Numbers

DP-860-PS2: With PS/2 cable  
DP-860-USB: With USB cable

## Features and Benefits

- Integrated HulaPoint II™ Pointing Device
- Lightweight ABS Polycarbonate Case
- 11.40" x 6.30" x 1.86" (w-h-d)
- USB and PS/2 configurations available
- 12 Function Keys
- 84-Key Functionality