

SLK-101

Backlit Industrial Keyboard

iKey's SLK-101 keyboard provides full-sized versatility in a rugged, compact design. For working in low-light areas, the SLK-101 keyboard is also available with optional backlighting. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the SLK-101 is ideal for use in environments ranging from manufacturing to material handling. The large numeric pad on the SLK-101 allows for easy data entry, while the robust polycarbonate case stands up in the roughest of conditions.



Technical Specifications

Certifications

NEMA 4X
UL60950, FCC Part 15 Class B

Key Switch

MATERIAL: Industrial silicone rubber
LIFE: 10 million cycles
TRAVEL: 0.055 in.
ACTUATION FORCE: 200g (+/- 20g)
FEEDBACK: Tactile with mechanical snap

Power

PS/2: 210mA@5V (from Keyboard port)
USB: 210mA@5V (from CPU port)

Temperature Range

STORAGE: -40C to +90C
OPERATING: -40C to +70C

Humidity

100%

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2 kHz
DURATION OF TEST PER AXIS: 3 hours

Flammability

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

Weight

1.5 lbs (0.68 kg)

Dimensions

14.60" x 5.55" x 0.92" (w-h-d)
370.8mm x 141mm x 23.4mm

Cable

LENGTH: 10' straight (3 m)
DESIGN: "Y" PS/2 or USB Cable

Compatibility

PS/2: All Windows Operating Systems
USB: All Windows and Macintosh OS

Warranty

1 year limited warranty

Model Numbers

SLK-101-PS2: With PS/2 cable
SLK-101-USB: With USB cable

Features and Benefits

- 14.60" x 5.55" x 0.92" (w-h-d)
- 10-Key Numeric Pad
- 12 Function Keys
- Integrated Backlighting
- MS Windows™ Function Keys
- Slim, Compact Design
- USB and PS/2 configurations available